

KTS-B Self-return Series
 (External spring)
 产品图片

Stroke range: 0-125mm,
 Analog output:0-5V,0-10V,4-20mA
 with 100mm shield wire;
 Suitable for narrow space situation,
 such as textile equipment, teaching
 and testing instruments, monitoring
 and control equipment etc.

| | | | | | | | | |
|---------------------------------|------------|-----------------|----|----|-----|-----|-----|-----|
| KTS-B Self-return Series | mm | 10 | 15 | 25 | 50 | 75 | 100 | 125 |
| Total Electrical Travel (T.E) | mm | 11 | 16 | 26 | 51 | 76 | 101 | 126 |
| Active Electrical Travel (A.E) | mm | 10 | 15 | 25 | 50 | 75 | 100 | 125 |
| Resistance Range $\pm 20\%$ | k Ω | 1.0 | | | 5.0 | | | |
| Independent Linearity | $\pm\%$ | 0.05 | | | | | | |
| Mechanical Travel (M.T) | mm | 11 | 16 | 26 | 51 | 75 | 101 | 126 |
| Output | | Voltage divider | | | | | | |
| Resolution | | Infinite | | | | | | |
| Operating Temperature | C° | -50 + 120 | | | | | | |
| Dimensions A | mm | 47 | 52 | 62 | 87 | 112 | 137 | 162 |

Dimensions for reference only and subject to change without prior notice.