

MINUO® 米诺 KTS-E 自復系列



可裝外置變送器, 自復式(外置彈簧)
 量程: 0-125mm, 可選模擬輸出:
 0-5V, 0-10V, 4-20mA 標準信號;
 標準100mm屏蔽綫引出。
 適應狹小的安裝位置, 如車檢測、
 自動化控制設備、實驗儀器等。

Self-return type (External spring)
 Stroke range: 0-125mm.
 Analog output: 0-5V, 0-10V, 4-20mA,
 with 100mm shield wire;
 Suitable for narrow space situation,
 such as vehicle detection, automatic
 control equipment, laboratory
 instruments etc.

KTS-E Series		5	10	15	25	50	75	100	125	\	\	\	\	\	\
Total Electrical Travel(T.E)電性總行程	mm	6	11	16	26	51	76	101	126	\	\	\	\	\	\
Active Electrical Travel(A.E)可用電性行程	mm	5	10	15	25	50	75	100	125	\	\	\	\	\	\
Resistance 電阻 ±20%	kΩ	1.0				5.0				\	\	\	\	\	\
Independent Linearity 獨立綫性率	± %	0.05													
Mechanical Travel 機械行程(M.T)	mm	6	11	16	26	51	75	101	126	\	\	\	\	\	\
Output range 輸出範圍		分压器 Voltage divider													
Resolution 解像度		infinite 無限													
Temperature Range 使用溫度範圍	°C	-50+120													
Dimensions 尺寸A	mm	42	47	52	62	87	112	137	162	\	\	\	\	\	\

尺寸僅供參考, 如有更改, 恕不另行通知
 Dimensions for reference only, subject to change without notice

Mechanical Dimension KTS-E 尺寸 KTS-E 自復式

