

# MINUO 米诺 KTS-B 自復系列 (彈簧外置)



量程: 0-125mm, 可定制供電AC24V  
可選模擬輸出: 0~5V, 0~10V, 4-20mA  
標準信號; 標準100mm屏蔽線引出,  
適應狹小的安裝位置, 如紡織設備、  
教學試驗儀器、測控設備等。

Stroke range: 0-125mm.  
Analog output: 0-5V, 0-10V, 4-20mA  
with 100mm shield wire;  
Suitable for narrow space situation,  
such as textile equipment, teaching  
test instrument, monitoring and  
control equipment etc.

KTS-B Series		5	10	15	25	50	75	100	125	\	\	\	\	\	\
Total Electrical Travel(T.E)電性總行程	mm	6	11	16	26	51	76	101	126	\	\	\	\	\	\
Active Electrical Travel(A.E)可用電性行程	mm	5	10	15	25	50	75	100	125	\	\	\	\	\	\
Resistance 電阻 ±20%	kΩ	1.0				5.0				\	\	\	\	\	\
Independent Linearity 獨立線性率	± %	0.05													
Mechanical Travel 機械行程(M.T)	mm	6	11	16	26	51	75	101	126	\	\	\	\	\	\
Output range 輸出範圍		分壓器 Voltage divider													
Resolution 解像度		infinite 無限													
Temperature Range 使用溫度範圍	℃	-50-120													
Dimensions 尺寸A	mm	42	47	52	62	87	112	137	162	\	\	\	\	\	\

尺寸僅供參考, 如有更改, 恕不另行通知  
Dimensions for reference only, subject to change without notice

## Mechanical Dimension KTS-B 尺寸 KTS-B 自復式

