

MINUO® 米诺 KTS-A 微型拉杆系列



可用外置模塊,
 量程: 0-125mm
 可選模擬輸出: 0~5V, 0~10V,
 4-20mA 標準信號;
 標準100mm 屏蔽線引出。
 適應狹小的安裝位置, 如行程檢
 測控制、試驗機、自動化設備等。

External connected signal processing,
 Stroke range: 0-125mm.
 Analog output: 0-5V, 0-10V, 4-20mA,
 with 100mm shield wire;
 Suitable for narrow space situation,
 such as stroke detection and control,
 testing machine, automation
 equipment etc.

KTS-A Series		5	10	15	25	50	75	100	125	\	\	\	\	\	\
Total Electrical Travel (T.E) 電性總行程	mm	6	11	16	26	51	76	101	126	\	\	\	\	\	\
Active Electrical Travel (A.E) 可用電性行程	mm	5	10	15	25	50	75	100	125	\	\	\	\	\	\
Resistance 電阻 ±20%	kΩ	1.0				5.0				\	\	\	\	\	\
Independent Linearity 獨立線性率	±%	0.05													
Mechanical Travel 機械行程 (M.T)	mm	6	11	16	26	51	75	101	126	\	\	\	\	\	\
Output range 輸出範圍		分压器 Voltage divider													
Resolution 解像度		infinite 無限													
Temperature Range 使用溫度範圍	°C	-50~120													
Dimensions 尺寸 A	mm	42	47	52	62	87	112	137	162	\	\	\	\	\	\

尺寸僅供參考, 如有更改, 恕不另行通知
 Dimensions for reference only, subject to change without notice

Mechanical Dimension KTS-A 尺寸 KTS-A 微型拉杆式

